

LA NOTTE REFRIGERATION



CONTRACTORS LICENSE #820340
AIR CONDITIONING *REFRIGERATION *HEATING
RESIDENTIAL *COMMERCIAL *INDUSTRIAL



Proposal Submitted To:

Vikeshni Diyal
&
Lori Hay

Work To Be Performed At:

Grayson Elementary
301 Howard
Westley, CA 95387

LaNotte Refrigeration proposes to furnish the following equipment. Production of listed items will commence upon receipt of an approved proposal, or purchase order.

Equipment:

➤ **Hood #1—Captive Air:**

- (1) 5424ND2PSPF 6ft 8" Long Exhaust Only Wall Canopy Hood with 16" Wide Front Perforated Supply Plenum with Built-in 3" Back Standoff
- (1) 430 SS where exposed.
- (1) Fire Cabinet on the Right Side 12.00" Width x 54.00" Length x 24.00" Height
- (4) FILTER 20" tall x 16" (19.625" by 15.625") wide Stainless Steel Captrate Solo filter with hook, ETL Listed. Particulate capture efficiency: 85% efficient at 9 microns, 76% efficient at 5 microns. Used on hoods shipped AFTER 7/27/17.
- (2) Recessed Allanson Round LED fixture and LED Light, 3500 K warm output.
- (1) EXHAUST RISER Factory installed 12" Diameter X 4" Height
- (2) SUPPLY RISER 12" x 28" Supply Riser with Volume Dampers
- (2) 1/2 Pint Grease Cup New Style, Flanged Slotted
- (1) FIELD WRAPPER 18.00" High Front, Right
- (1) Electrical Package Installation in Utility Cabinet by Plant.
- (1) BACKSPLASH 120.00" High X 98.00" Long 430 SS Vertical (Includes End Caps & Divider Bars)
- (1) LEFT END STANDOFF 1" Wide 54" Long Insulated
- (1) LEFT SIDESPLASH 120.00" High X 72.00" Long 430 SS Vertical (Includes End Caps & Divider Bars)

➤ **Fire System #1:**

- (1) TANKSP1 Tank Fire Suppression 4 gallon Fire System in Utility Cabinet (includes pre-piped hood(s) with electric detection, tank(s), 24 VDC release mechanism, fire system agent, pressurized tanks, and electric pull station). (Formerly CASEWC). Includes piping for hood: 1.
- (1) Tank-based Fire Protection System equipped with Electronic Detection utilizing CORE board as a Listed Release Mechanism. Installed in Hood Utility Cabinet with integral hood prewire panel.
- (1) Pressure Switch Monitors Tank Pressure, Supervised Signal, TANK FIRE SUPPRESSION

Continued below...

1835 S. Van Ness Ave. Fresno, CA 93721
Toll Free: 1-877-277-1860 Phone: (559) 277-1860 Fax: (559) 277-1859
e-mail- ccostalanotte@gmail.com

LA NOTTE REFRIGERATION



CONTRACTORS LICENSE #820340
AIR CONDITIONING *REFRIGERATION *HEATING
RESIDENTIAL *COMMERCIAL *INDUSTRIAL



➤ **Fan #1 DU85HFA-Exhaust Fan:**

- (1) *DU85HFA High Speed Direct Drive Centrifugal Upblast Exhaust Fan with speed control (speed control included for single phase only), disconnect switch and 15-3/4" wheel. Exhaust fan handles 1333 CFM @ -0.900"wc ESP, fan runs at 1147 RPM. Exhaust motor: 0.750 HP, 1ph, 115v, 60Hz, 8.8 FLA, ODP-ECM (Open drip proof electronically commutated motor).*
- (1) *Grease cup for kitchen-duty centrifugal exhaust fans, box dimensions 17-1/8 L x 5-1/16 W x 3-3/4 H (18 GA) (Includes down spout).*
- (1) *Gasketing: Thermeez Woven Ceramic Tape-1/4" x 1" with adhesive back-Max temp 1500 F. To be applied between fan base and grease duct. Installed under fan base 1/2" from the inside edge of the base to match up with the curb top flanges.*
- (1) *ECM wiring package for exhaust motors with PWM signal from ECPMO3 prewire.*
- (1) *CAT5E CABLE 25 Foot.*
- (1) *Curb CRB23x20E on fan #1 flat curb.*
- (1) *Hinged base for curb. Standard hinge attached to curb. Used on fans with wheels 20" or smaller. 12 GA galvanized.*
- (1) *Vented base for curb.*

➤ **Fan #2 A1-15D-Supply Fan:**

- (1) *A1-15D untempered supply unit with 15" direct drive fan in size #1 housing. Supply fan handles 1200 CFM @ 0.400"wc ESP, fan runs at 1471 RPM. Supply motor: 1.000HP, 1ph, 115v, 60Hz, 10.2 FLA, ODP-ECM (Open drip proof electronically commutated motor). Down discharge-Air flow right -> left.*
- (1) *Celdek evaporative cooler for size #1 modular un-tempered supply air unit. 36.75" wide x 32.125" long x 36.688" high. For outdoor installation. Minimum water pressure for optimal performance is 30 PSI. Maximum water pressure should not exceed 50 PSI. Use with water softener recommended.*
- (1) *Sloped filtered intake for size #1 modular untempered supply unit. 26.813" wide x 53.625" long x 31.313" high. Includes 2" MV EZ Kleen Metal Mesh Filters.*
- (1) *120v wiring connection to energize evaporative coolers from untempered supply fans.*
- (1) *ECM Wiring Package MODBUS Control for Supply EC motors. MSC Controller.*
- (1) *CAT5E CABLE 50 Foot. UV rated.*
- (1) *Curb CRB21x20 on fan #2 flat curb.*
- (1) *Rail ADJUSTLEG-36 (Set of 2) on fan #2.*

Continued below...

1835 S. Van Ness Ave. Fresno, CA 93721
Toll Free: 1-877-277-1860 Phone: (559) 277-1860 Fax: (559) 277-1859
e-mail- ccostalanotte@gmail.com

LA NOTTE REFRIGERATION



CONTRACTORS LICENSE #820340
AIR CONDITIONING *REFRIGERATION *HEATING
RESIDENTIAL *COMMERCIAL *INDUSTRIAL



➤ **Electrical System #1:**

- (1) DCV-1111 Demand Control Ventilation, w/control for 1 Exhaust fan, 1 supply fan, exhaust on in fire, lights out in fire, fans modulate based on duct temperature. Inverter duty 3 phase motor required for use with VFD. Room temperature sensor shipped loose for field installation. Verify distance between VFD and motor; additional cost could apply if distance exceeds 50ft. Includes 1 duct thermostat kit.
- (1) VERIZON CELLULAR KIT, WIRED ANTENNA AND VERIZON DATA FOR 1 YEARS.
- (1) PSP thermostat kit, includes 1x duct thermostat, quick seal, and j-box for monitoring of PSP discharge temperature.
- (1) Digital Prewire Lighting Relay Kit. Includes hood lighting relay & terminal blocks. Allows for up to 1400W of lighting each.
- (1) Thermistor CABLE 18/2 AWG GREEN WHITE, plenum rated. USED for thermistor duct stat. Per Foot Price.
- (1) CAT5E CABLE 25 Foot.

➤ **Duct Run #1:**

- (1) (RC1) DW16DWRISER2RS Double Wall Riser Cover Used On 12" Inner Riser, 4" long 2 Layers Reduced Clearance 16" Stainless Steel Outer Riser Shell Assembly. Includes Insulation & Single V Clamps For Inner & Outer Connections.
- (1) (P1) DW1245DWASY2RS Double Wall Duct 12" Inner 45 Duct 2 Layers Reduced Clearance 16" Stainless Steel Outer Shell.
- (1) (P2) DW1245DWASY2RS Double Wall Duct 12" Inner 45 Duct 2 Layers Reduced Clearance 16" Stainless Steel Outer Shell.
- (1) (P3) DW1227DWAJD2RS Double Wall Adjustable Duct 12" Inner Duct 2 Layers Reduced Clearance 16" Stainless Steel Outer Shell. Min Length = 11" / Max Length = 24.5" / Adjustment = 13.5" / Adjustable Section May Need To Be Cut. Includes single and double wall "V" Clamps.
- (1) (P4) DW1235DWLTTP2RS Double Wall Duct 12" Inner Duct, 35" long 2 Layers Reduced Clearance 16" Stainless Steel Outer Shell Used With Transition Plate.
- (1) (P5) DW2312TPDBEX Duct to Curb Transition 3/4" Down Turn, 23" Curb to 12" Duct, 16 GA Aluminized. Used on NCA14FA & NCA14HPFA. Transition Plate OD is 23.5" Designed For Use With Exhaust Fan. NonStandard Part.
- (1) 3M2000PLUS Duct 3M Fire Barrier 2000 Plus Silicone Used as sealant to Seal Duct Joints.
- (1) DW12DWCLASY2RS Duct 12" Duct 16" Double "V" Clamp 2R Insulation & Single "V" Clamp Included Reduced Clearance.

Continued below...

LA NOTTE REFRIGERATION



CONTRACTORS LICENSE #820340
AIR CONDITIONING *REFRIGERATION *HEATING
RESIDENTIAL *COMMERCIAL *INDUSTRIAL



➤ **Factory Services:**

- (1) Service design verification for CASLink Ethernet.
- (1) Service design verification for Demand Control Ventilation
- (1) Service design verification for Evap Cooler.
- (1) Service design verification for Exhaust Fan.
- (1) Service design verification for Hood.
- (1) Service design verification for Untempered Supply Fan

Total Material Price: \$27,950.00

Respectfully Submitted by: _____ Date: 3.15.2022
Frank LaNotte – Owner

Acceptance of proposal:

The above prices, specifications and conditions are satisfactory and are hereby accepted. You are authorized to do work as specified. Payment will be made as outlined above.

IF THIS ACCOUNT IS REFERRED TO ANY ATTORNEY(S) FOR COLLECTION REGARDLESS OF THE OUTCOME **DEBTOR AGREES TO PAY ATTORNEY'S FEES TO SELLER'S ATTORNEY AND FULL COST IN THE EVENT SUIT IS FILED AND IN CASE DEBTOR AND/OR ANY OF THE CO-DEFENDANTS OR CO-PARTICIPANTS PREVAIL AGAINST SELLER, NO ATTORNEY'S FEES AND COST CAN BE CLAIMED AGAINST SELLER AS DEBTOR IS LIABLE FOR ALL ATTORNEY'S FEES AND COURT COST, EVEN IF SELLER FILES AGAINST THE INCORRECT DEFENDANT(S) AND OR DEFENDANT(S) STATUS. ATTORNEY'S FEES FOR THE ENTIRE AMOUNT CLAIMED IN A COMPLAINT WILL BE ALLOWED EVEN THOUGH ONLY ONE MORE INVOICES ARE SIGNED BY DEBTOR**

Signature _____

Print _____

Date _____

1835 S. Van Ness Ave. Fresno, CA 93721
Toll Free: 1-877-277-1860 Phone: (559) 277-1860 Fax: (559) 277-1859
e-mail- ccostalanotte@gmail.com